



Solid KitBin (#IBCK100SGR)



Vented KitBin (#IBCK100VGR)

Specifications

External Dimensions (mm)	1200 x 1000 x 715 (H)
Internal Dimensions (mm)	1116 x 916 x 565 (H)
Tare Weight (KG)	38 Kg
Volume (L)	600L
Maximum Load (Single)	600 Kg
Maximum Stacking Load	3000 Kg

Features

- 5 units stack in the footprint of 1
- Pallet can be used separately
- Easy to assemble without tools
- Hygienic all plastic design
- 4 way forklift and pallet jack entry
- Combination of solid and vented walls available. For example, solid walls with vented base
- Interlocking foot design for safe stacking
- Reinforced base to prevent sagging
- Non porous surface prevents mould or bacteria growth
- Available with lids
- Available in solid or vented

Benefits


- Save up to 63% of storage space
- Reduce OH & S concerns with walk-in loading / unloading
- Accessible 4 way entry by operator
- Panels are interchangeable and can be replaced individually. Cuts replacement and inventory costs.
- One of the highest strength-to-weight ratios in the world
- Smooth surfaces for easy cleaning and product protection
- No splinters, rust or paint chips

Options

Half Height



One & A half height



Double Height



Triple Height



*Please see www.nayla.com for full specifications of Option KitBins. Also available in 'Two & A Half' height.

Customize


Lids



Dolly Frame



Company Logos



Contact Us

Phone: + 61 0 2 9678 9200
Fax: + 61 02 9678 9755
Web: www.nayla.com
Address: Unit 11, 55 Fourth Avenue, Blacktown, NSW, 2148, Australia